FLUORO RUBBER COMPOSITION

Patent number:

JP1306454

Publication date:

1989-12-11

Inventor:

SONOI TAKEHIRO; others: 01

Applicant:

NIPPON MEKTRON LTD

Classification:

- international:

C08L27/12; C08K3/22; C08K5/34

- european:

Application number:

JP19880135421 19880603

Priority number(s):

Report a data error he

Also published as:

📆 DE3915318 (A[.]

Abstract of JP1306454

PURPOSE:To obtain a fluoro rubber composition having improved hygroscopicity, handling properties, stability, etc., as well as excellent curing physical properties, shaping properties, etc., by blending a fluor rubber with a specific quaternary ammonium salt compound used as a curing accelerator. CONSTITUTION:(A) 100 pts. wt. fluoro rubber is blended with (B) 1-40 pts. wt., preferably 3-15 pts.wt. oxide and/or hydroxide of bivalent metal (e.g., magnesium or calcium), (C) 0.5-10 pts.wt. preferably 0.5-6 pts.wt. polyhydroxy aromatic compound (e.g., bisphenol A) and (D) 0.1-5 pts.wt., preferably 0.1-2 pts. wt quaternary salt compound expressed by the formula (R is 1-24C alkyl or 7-20C aralkyl; X<-> is tetrafluoroborate, etc.).

Data supplied from the esp@cenet database - Patent Abstracts of Japan